

WALL ROLL-UP SCREEN

5 TECHNICAL FIELD

The present invention relates to a track type wall roll-up screen among portable screens for projection, and more particularly, to a wall roll-up screen wherein the screen can be used and portable with ease by attaching a magnet assembly to both sides of a lower rod of the screen.

10

BACKGROUND ART

In a conventional wall roll-up screen as shown in FIG. 1, it is necessary to roll up the screen 10 around a lower rod like a scroll and to tie the screen with string 11 so as to reserve it, and to untie the string 11 to use the screen 10.

15 And, when a user wishes to carry the screen, the user has to tie it with the string 11, which is troublesome. Especially, in this case, a surface of the screen where the string is tied has some wrinkles and edges of the screen can be loosish since the upper and lower rods are wrenched mutually. Besides the problems described above, the beauty of product is deteriorated in appearance.

20

DISCLOSURE OF INVENTION

The present invention has been made in view of the above problems, and it is an object of the present invention to provide a wall roll-up screen among portable screens for projection, especially, a wall roll-up screen wherein

the screen can be used and portable with ease by attaching a magnet assembly to both sides of a lower rod of the screen.

5 According to the present invention for achieving the object, there is provided a wall roll-up screen wherein a screen is attached between upper and lower rods and the screen can be rolled up by the lower rod, wherein groove shaped rings processed with a magnetic material such as steel are attached on left and right ends of the upper rod of the screen and magnets is
10 coupled on left and right ends of the lower rod of the screen, so that the screen is rolled up and then the magnets of the left and right of the lower rod are coupled with the groove shaped rings of the upper rod when the screen is carried, and the magnets and the groove shaped rings are separated when the screen is used.

15 Preferably, the groove shaped rings have grooves where the magnet can be coupled with the inner part of the groove shaped rings.

 Preferably, separate attachment units are attached on the wall in the rear part of the upper and lower rods, and the attachment units are coupled with the upper and lower rods of the screen so that the screen is stably and fixedly
20 attached to the wall.

 Preferably, the groove shaped rings of the upper rod and the magnets of the lower rod can be exchanged in their positions.

BRIEF DESCRIPTION OF THE DRAWINGS

The above and other objects and features of the present invention will
5 become apparent the following description of preferred embodiment of given in
conjunction with the accompanying drawings, in which:

FIG. 1 is an explanatory view of a wall roll-up screen in the art;

FIG. 2 is an explanatory view of an external shape of a screen in
accordance with the present invention;

10 FIG. 3 is an explanatory view of a magnet of a screen in accordance
with the present invention;

FIG. 4 is a detailed explanatory view of a magnet of a screen in
accordance with the present invention;

15 FIG. 5 is an explanatory view of a magnet contact of a screen in
accordance with the present invention;

FIG. 6 is an explanatory view of a screen of the present invention when
the screen is applicably used;

FIG. 7 is an explanatory view of a screen of the present invention when
the screen is fixedly used with a stand; and

20 FIG. 8 is an explanatory view of a construction of a screen in
accordance with the present invention when the screen is applicably used.

BEST MODE FOR CARRYING OUT THE INVENTION

The present invention will now be described more fully hereinafter with

reference to the accompanying drawings, in which preferred embodiments of the invention are shown. This invention may, however, be embodied in different
5 forms and should not be construed as limited to the embodiments set fourth herein. Rather, these embodiments are provided so that this disclosure will be thorough and complete, and will fully convey the scope of the invention to those skilled in the art. In the drawings, like numbers refer to like elements throughout the specification.

10 The screen of the present invention can be used and portable with ease by attaching a magnet assembly to both sides of a lower rod of the screen. When the screen is used, the lower rod 2 is separated from an upper rod 1 of the screen 3 to be extended. And, when the screen is carried, the screen 3 is rolled up and the upper and lower rods 1 and 2 are attached each other so that
15 it is convenient to carry the screen without any damage on the surface of the screen and there is no distortion of the upper and lower rods of the screen in the right and left directions.

Referring to FIGS. 2 and 3, the present invention has the upper and lower rods 1 and 2, and the screen 3 is attached between the rods 1 and 2 so
20 that the lower rod 2 is rolled up when the screen is moved and the rod 2 is extended when the screen is used.

Groove shaped rings 4 are attached to right and left sides of the upper rod 1, which is made of steel or the like responding to a magnetic property, and magnets 5 are attached on right and left ends of the lower rod 2.

Such a construction may be changed, that is, the groove shaped rings 4 and the magnets 5 of the upper rod 1 and the groove shaped ring 4 may be
5 exchanged in their positions.

As shown in FIG. 6, a well known attachment unit 6 such as a rubber
adsorption plate or a snap button which can be attached and separated easily
may be coupled in the rear part of the upper rod 1. And, a groove shaped ring 4
is constructed in the rear part of the lower rod 2, which is separated from the
10 lower rod 2, and there is an attachment unit 7 behind the lower rod 2.

There exist grooves into which magnets having L or U shape can be
inserted in the middle of the groove shaped rings 4.

Referring to FIG. 7, a known screen support 8 can be coupled and used
fixedly in answer to a need, and the screen 3 may be a projection screen of roll
15 shape.

Referring to FIG. 8, a support 9 forming an insertion unit 10 into which
the lower rod 2 is inserted is constructed on both ends of the upper rod 1, the
groove shaped ring 4 formed of steel is constructed as a portion of a circle, and
a handle 11 is constructed on both ends of the magnet of the lower rod 2.

20 The upper and lower rods 1 and 2 are extended when the screen is
used, as shown in FIG. 2a. And, when the screen is portable and carried, the
screen attached to the lower rod 2 is rolled up around the lower rod 2 and then
the magnets 5 attached to the right and left ends of the lower rod 2 are attached
to the groove shaped rings 4 formed of the steel which are attached to the right

and left parts of the upper rod 1.

Referring to FIG. 4, the screen of the present invention has an
5 increased attachment effect by coupling the magnets 5 to the inner groove
areas of the right and left parts of the upper rod 1.

That is, as shown in FIG. 5, groove shaped rings 4 and magnets 5 on
both ends of the upper and lower rods 1 and 2 of the present invention should
be of circle shapes since the upper and lower rods 1 and 2 should be adhered
10 closely each other after the screen 3 is rolled up around the lower rod 2.

In case that the grooves 4 and magnets 5 on both ends of the upper
and lower rods 1 and 2 are formed of circle shape only, the coupling contact A
becomes very small as shown in FIG. 5a so that the upper and lower rods 1 and
2 are easily separated with small force.

15 However, in case that there are grooves in the groove shaped rings 4
which can be coupled with the magnets 5 as shown in the present invention,
since the coupling contact B is extended to the right and left parts of the
magnets and to the front and rear parts of the groove shaped rings 4, the
coupling forces of the magnets 5 and the groove shaped rings 4 can be strong.
20 Additionally, since the magnets 5 of the lower rod 2 which are coupled with the
right and left ends of the groove shaped rings 4 are not twisted in the right and
left directions, the extension of the screen in its right and left parts can be
protected.

Also, as shown in FIG. 6, since the screen of the present invention is

conveniently installed on the wall when the attachment unit 6 is coupled with the rear part of the upper rod 1 and the upper rod is coupled with the lower rod by the magnets 5 when the lower rod 2 is rolled up, there is no damage on the screen at all.

Also, as shown in FIG. 8, the lower rod 2 which is inserted into the insertion units 10 on both ends of the upper rod 1 has magnets 5 on its groove shaped rings 4 so that there is an effect that both rods do not apart from each other, and the screen 3 of the lower rod 2 is stably rolled up to be carried when the lower rod 2 is rolled up by turning the handle 11.

INDUSTRIAL APPLICABILITY

In accordance with the present invention, it is convenient to roll up a screen itself of a front screen or a projection screen or to extend it, to maintain its beauty of appearance without tying the screen with string, to attach it to a wall or a ceil simply, to fix it in order that the screen 3 is not shaken, and to carry it stably since upper and lower rods 1 and 2 are not twisted.

When the screen of the present invention is used, the groove shaped rings 4 are attached to the attachment units 6 behind the lower rod 2 and the magnets 5 of the lower rod 2 are attached to the coupling attachment units 7 which have been attached to the coupling wall rear already so that the screen is used as portable, home and conference screens.